



COLUMBUS CHEMICAL INDUSTRIES INC.

P.O. BOX 8
COLUMBUS, WISCONSIN 53925-0008
(920) 623-2140
FAX (920) 623-2577

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Ammonium Acetate

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturers /Distributor Address Number Street City State and Zip Code

Columbus Chemical Industries

N4335 Temkin Road

Columbus, Wisconsin 53925

Emergency Telephone Number

CHEMTREC 1 (800) 424-9300

Telephone Number for Information

1-920-623-2140

Date Prepared

04-10-2006

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Table with 6 columns: Hazardous Components (Specific Chemical Identity, Common Name(s)), CAS #, OSHA PEL, ACGIH TLV, Other Limits Recommended, % (optional). Row 1: Ammonium Acetate, 631-61-8, 15 mg/m³ (dust), 10 mg/m³ (dust), Not available.

Section III - Physical/Chemical Characteristics

Table with 2 columns: Property, Value. Rows: Boiling Point (Not available), Vapor Pressure (mm Hg) (Not available), Vapor Density (AIR = 1) (Not available), Specific Gravity (H2O = 1) (Not available), Melting Point (114°C(237°F)), Evaporation Rate (Butyl Acetate = 1) (Not available).

Solubility in Water

Complete.

Appearance and Odor

White crystalline solid.

Section IV Fire and Explosion Hazard Data

Table with 4 columns: Flash Point (Method Used), Flammable Limits, LEL, UEL. Row 1: Nonflammable, Not applicable, Not applicable.

Extinguishing Media

Water spray, dry chemical, carbon dioxide, alcohol foam.

Special Fire Fighting Procedures

In the event of a fire, wear full protective clothing and NIOSH/MSHA-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Prevent contact with skin and eyes.

Unusual Fire and Explosion Hazards

Emits toxic fumes under fire conditions.

Section V Reactivity Data

| | | | | |
|-----------|----------|---|---------------------|---|
| Stability | Unstable | | Conditions to Avoid | Strong oxidizing agents, heat, incompatibles. |
| | Stable | X | | |

Incompatibility Materials to Avoid

Oxidizers, acids. Calcium, lithium, magnesium, sodium, potassium metals.

Hazardous Decomposition or Byproducts

Carbon dioxide, carbon monoxide, acetic acid, ammonia, nitrogen oxides.

Hazardous Polymerization**Conditions to Avoid**

| | | | |
|--|----------------|---|----------------|
| | May Occur | | Not available. |
| | Will Not Occur | X | |

Section VI Health Hazard Data

| Routes of Entry | Inhalation ? | Skin ? | Ingestion ? |
|-----------------|--------------|--------|-------------|
| | Yes | Yes | Yes |

Health Hazards (Acute and Chronic)

Irritating to the skin, eyes, mucous membranes and upper respiratory tract. May be harmful if swallowed. Inhalation may result in spasm, inflammation and edema of the larynx and bronchi, chemical pneumonitis, and pulmonary edema. Ingestion may result in irritation of the gastrointestinal tract and possible ammonia poisoning.

| Carcinogenicity | NTP | IARC Monographs | OSHA REGULATED? |
|-----------------|------------|-----------------|-----------------|
| | Not listed | Not listed | Not listed |

Signs and Symptoms of Exposure.

Burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, vomiting, erythema, blisters,

tissue destruction, bloody diarrhea, edema, convulsions, bronchitis, pneumonia, cardiovascular collapse, shock.

Medical Conditions Generally Aggravated by Exposure

Expected to aggravate asthma, emphysema, other respiratory diseases and existing

dermatitis.

Emergency and First Aid Procedures

EYES/SKIN: Flush immediately with plenty of water for at least 15 minutes. Remove

contaminated clothing. Remove contact lenses if possible. Call physician if irritation develops. Wash clothing

before reuse. **INGESTION:** DO NOT induce vomiting. Give several cups of water to conscious victim. Call a physician.

INHALATION: Move to fresh air. Give oxygen if breathing is difficult, artificial respiration if not breathing.

Section VII Precautions for Safe Handling and Use**Steps to be Taken in Case Material is Released or Spilled**

Evacuate unprotected personnel from area. Eliminate all ignition sources. Ventilate spill area.

Wear self-contained breathing apparatus rubber boots, heavy protective gloves and chemical safety goggles.

Sweep up spilled material and place into a container for disposal. Flush spill area with water.

Waste Disposal Method Dispose of material in accordance with all Federal, state, and local regulations.

Precautions to be Taken in Handling and Storing

Keep in tightly-closed, plainly-labelled containers, stored in a cool, dry, ventilated area. Protect against physical damage and light. Keep away from heat, sparks and flame. Maintain adequate ventilation.

Material may evolve ammonia.

Other Precautions Containers, even when empty, will retain residue. Always obey hazard warnings and handle empty

containers as if they were full.

Section VII Control Measures

Respiratory Protection (Specify Type) NIOSH/MSHA-approved respirator with dust/mist cartridge.

| | | | | |
|-------------|----------------------|--------------|---------|--------------------------|
| Ventilation | Local Exhaust | Recommended. | Special | Safety shower nearby. |
| | Mechanical (General) | Recommended. | Other | Eye wash station nearby. |

Protective Gloves Appropriate chemical-resistant gloves. **Eye Protection** Chemical Safety Goggles.

Other Protective Clothing or Equipment Boots; clean body-covering clothing; full-face respirator, if needed.

Work /Hygienic Practices Do **NOT** wear contact lenses. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid breathing vapors. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid prolonged or repeated exposure.

Columbus Chemical Industries, Inc. ("Columbus") believes that the information herein is factual but it is not intended to be all inclusive. The information relates only to the specific Material designated and does not relate to its use in combination with other materials or its use as to any particular process. Because safety standards and regulations are subject to change and because Columbus has no continuing control over the Material, those handling, storing or using the Material should satisfy themselves that they have current information regarding the particular way the Material is handled, stored and used and that the same is done in accordance with federal, state and local law. COLUMBUS MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR USE.