



**COLUMBUS CHEMICAL INDUSTRIES INC.**

P.O. BOX 8  
 COLUMBUS, WISCONSIN 53925-0008  
 (920) 623-2140  
 FAX (920) 623-2577

**Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements

**U.S. Department of Labor**

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

**IDENTITY (as Used on Label and List)**

**Gelatin**

**Note:** Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

**Section I**

Manufacturers /Distributor Address Number Street City State and Zip Code

Columbus Chemical Industries  
 N4335 Temkin Road  
 Columbus, Wisconsin 53925

Emergency Telephone Number

CHEMTREC 1 (800) 424-9300

Telephone Number for Information

1-920-623-2140

Date Prepared

12-18-2007

Signature of Preparer (optional)

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Name(s))	CAS #	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Gelatin/protein	9000-70-8	Not Available	Not Available	Not Available	

**Section III - Physical/Chemical Characteristics**

Boiling Point	Not Available	Specific Gravity (H <sub>2</sub> O = 1)	Not Available
Vapor Pressure (mm Hg)	Not Available	Melting Point	Not Available
Vapor Density (AIR = 1)	Not Available	Evaporation Rate (Butyl Acetate = 1)	Not Available

Solubility in Water

Complete

Appearance and Odor

White to beige colored crystals or powder

**Section IV Fire and Explosion Hazard Data**

Flash Point (Method Used)	Flammable Limits	LEL	UEL
Not Flammable		Not Applicable	Not Applicable

Extinguishing Media

Water spray, dry chemical, carbon dioxide, alcohol foam.

Special Fire Fighting Procedures

In the event of a fire, wear full protective clothing and NIOSH/MSHA-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

Unusual Fire and Explosion Hazards

May release toxic fumes