



COLUMBUS CHEMICAL INDUSTRIES INC.

P.O. BOX 8
COLUMBUS, WISCONSIN 53925-0008
(920) 623-2140
FAX (920) 623-2577

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Potassium Chromate, 5% Aqueous

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturers /Distributor Address Number Street City State and Zip Code

Columbus Chemical Industries, Inc.

N4335 Temkin Road

Columbus, Wisconsin 53925

Emergency Telephone Number

CHEMTREC 1 (800) 424-9300

Telephone Number for Information

(920) 623-2140

Date Prepared

03-03-2006

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Table with 6 columns: Hazardous Components, CAS #, OSHA PEL, ACGIH TLV, Other Limits Recommended, % (optional). Row 1: Potassium Chromate*, 7789-00-6, 0.5 ug/m³, 0.01mg/m³ Cr, 0.001 mg/m³ REL, 5%. Includes Action Level: 1 ug/m³ TWA.

*Regulated under OSHA 1910.1026

Section III - Physical/Chemical Characteristics

Table with 4 columns: Property, Value, Property, Value. Rows: Boiling Point (Not available), Specific Gravity (1.0089), Vapor Pressure (Not applicable), Melting Point (Not available), Vapor Density (Not available), Evaporation Rate (Not available).

Solubility in Water

Soluble

Appearance and Odor

Yellow translucent liquid

Section IV Fire and Explosion Hazard Data

Table with 4 columns: Flash Point, Flammable Limits, LEL, UEL. Row 1: Not flammable, Not applicable, Not applicable, Not applicable.

Extinguishing Media

Water spray, dry chemical, carbon dioxide, alcohol foam. Use methods appropriate for surrounding fire.

Special Fire Fighting Procedures

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece respirator operated in positive pressure mode. Cool fire-exposed containers.

Unusual Fire and Explosion Hazards

Emits toxic fumes under fire conditions.

Section V Reactivity Data

Stability	Unstable		Conditions to Avoid	Excessive heat, incompatible
	Stable	X	materials	

Incompatibility Materials to Avoid

Combustible materials, strong reducing agents, light.

Hazardous Decomposition or Byproducts

Potassium oxides, Chromium oxides, carbon oxides.

Hazardous Polymerization**Conditions to Avoid**

	May Occur		Not applicable.
	Will Not Occur	X	

Section VI Health Hazard Data

Routes of Entry	Inhalation ?	Skin ?	Ingestion ?
	Yes	Yes	Yes

Health Hazards (Acute and Chronic)

SKIN: Causes irritation. EYES: Causes eye irritation. INHALATION: Causes irritation to mucous membranes and upper respiratory tract. INGESTION: Harmful and may be fatal if swallowed. Toxic effects may not be immediately detected.

Chronic: Kidney or liver damage. **Known carcinogen - Potassium Chromate.**

Carcinogenicity	NTP	IARC Monographs	OSHA REGULATED?
	Known - Chromium	Group 1 - Chromium	Yes: 1910.1026

Signs and Symptoms of Exposure.

Burning, itching, redness, pain of mucous membranes, skin and eyes. Headache, nausea, vomiting, dizziness, drowsiness, weakness, edema, chest pains, gastrointestinal disturbances, difficulty breathing. SKIN/EYES: Itchiness, redness, pain, swelling,

Medical Conditions Generally Aggravated by Exposure

Unknown

Emergency and First Aid Procedures

INGESTION: If swallowed, wash out mouth with water provided person is conscious, Call physician immediately. EYES: Immediately flush with large amounts of water for at least 20 minutes. Call a physician. INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician. SKIN: Immediately wash skin with soap and large amounts of water.

Section VII Precautions for Safe Handling and Use**Steps to be Taken in Case Material is Released or Spilled**

Evacuate personnel from area. Wear chemical-resistant goggles, rubber boots, apron and rubber gloves. Absorb on suitable material and hold for waste disposal. Avoid contact, inhalation and ingestion. Ventilate area and wash spill site after material pickup is complete. Prevent release to environment.

Waste Disposal Method Dispose of spillage, empty containers and other materials used for cleanup in compliance with all applicable Federal, state and local regulations. U170 and D007 RCRA waste codes.

Precautions to be Taken in Handling and Storing Keep in tightly closed plainly-labelled containers, stored in a cool, dry, ventilated area. Protect against physical damage, air and light. Maintain adequate ventilation. Store below 80 °F (27 °C). Do not breathe or ingest. Avoid contact with skin or eyes. Wash thoroughly after handling.

Other Precautions Containers, even when empty, will retain residue and vapors. Always obey hazard warnings and containers as if they were full. Avoid raising dust. **DO NOT INGEST!**

Section VII Control Measures

Respiratory Protection (Specify Type) NIOSH/MSHA-approved respirator with dust/mist cartridge if high amounts of dust or fume.

Ventilation	Local Exhaust	Necessary.	Special	Eye wash nearby.
	Mechanical (General)	Recommended.	Other	Safety shower nearby.

Protective Gloves Appropriate chemical resistant gloves. **Eye Protection** Chemical goggles.

Other Protective Clothing or Equipment Chemical-resistant boots and apron.

Work /Hygienic Practices Contact lenses should not be worn when working with this material. Avoid eye and skin contact.

Do not breathe vapors. Wash thoroughly after handling. Avoid prolonged or repeated exposure.

Maintain eye wash station and quick-drench facilities in work area. **CARCINOGEN!**

Columbus Chemical Industries, Inc. ("Columbus") believes that the information herein is factual but it is not intended to be all inclusive. The information relates only to the specific Material designated and does not relate to its use in combination with other materials or its use as to any particular process. Because safety standards and regulations are subject to change and because Columbus has no continuing control over the Material, those handling, storing or using the Material should satisfy themselves that they have current information regarding the particular way the Material is handled, stored and used and that the same is done in accordance with federal, state and local law. COLUMBUS MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR